




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61M 16/10, 16/00	A1	(11) International Publication Number: WO 91/19527 (43) International Publication Date: 26 December 1991 (26.12.91)
<p>(21) International Application Number: PCT/BE91/00038</p> <p>(22) International Filing Date: 17 June 1991 (17.06.91)</p> <p>(30) Priority data: 9000619 18 June 1990 (18.06.90) BE 9001198 14 December 1990 (14.12.90) BE</p> <p>(71) Applicant (for all designated States except US): PONNET, GILMAN EN ANTHONY [BE/BE]; Vogelkerslaan 20, B-2950 Kapellen (BE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only) : ANTHONY, Jean-Michel [BE/BE]; Ringlaan 78, B-2610 Wilrijk (BE).</p> <p>(74) Agent: VOSSWINKEL, P.; Bureau Gevers S.A., Rue de Li-vourne 7, Bte 1, B-1050 Brussels (BE).</p>	<p>(81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), NL (European patent), SE (European patent), US.</p> <p>Published With international search report.</p>	
(54) Title: A DEVICE FOR COMPENSATING FOR THE MOISTURE AND HEAT LOSSES FROM AN ARTIFICIAL NOSE		



(57) Abstract

A device for compensating for the moisture and heat losses occurring in artificial noses to be incorporated in the duct for supplying air and/or gasses to a patient and which is composed of a chamber (1) used as actual artificial nose wherein a hygros-copic material (7) serving as a buffer is provided, with means to maintain the in- an exhaled between the artificial nose and the

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

- 1 -

"A device for compensating for the moisture
and heat losses from an artificial nose".

This invention relates to a device for compensating for the moisture and heat losses from an artificial nose used with a patient.

Artificial noses are devices which are incorporated
5 in a duct between a patient and a machine, usually known as a ventilator, in order to allow the patient to recuperate a portion of the moisture and heat comprised in his exhaled air. Artificial noses are mainly used for anesthesia and/or for artificial respiration, such
10 artificial noses including a buffer, i.e. the moisture exchanger element, generally called HME.

In many cases, such a device is not sufficient for maintaining the humidity and the temperature on the desired level.

Indeed, different types of artificial noses have the very serious drawback of involving, in the most advantageous
15 circumstances, a moisture and heat loss of about 30 %.

Therefore, an object of the invention is to prescribe a device which solves the hereabove mentioned problem in a reliable way and which assures therefore the required humidity and temperature level of the air and/or mixture of air and gasses supplied
20 to the patient, whatever may be the shortcomings of the artificial nose which is also known in the technical jargon as "heat moisture exchanger or HME".

In order to realize this according to the invention, the device according to the invention is provided to be incorporated in
25 the duct for supplying air and/or gasses to a patient and is composed of a chamber used as actual artificial nose wherein a hygroscopic material serving as a buffer is provided, with means being provided to maintain the air in- and exhaled by the patient, at the required heat level, between the artificial nose and the patient.

30

- 2 -

In the most advantageous embodiment, said means is a heating resistance which is positioned at a distance from said hygroscopic material.

According to a possible embodiment, said
5 resistance is mounted in said chamber.

According to a possible variant, said resistance is mounted outside said chamber, between this chamber and the patient.

It is advisable that said resistance is externally water-absorbent and means are provided for supplying water to this
10 resistance.

According to a possible embodiment, said resistance is enclosed by a sleeve composed of a water-absorbent textile to which water is supplied.

According to another possible embodiment, said
15 resistance is composed of a textile, at least a part of the weft and/or warp threads of which consist of heating resistances.

Other details and advantages of the invention will become apparent from the following description of a device for compensating for the moisture and heat losses from an artificial nose used with a patient according to the invention. This description is only
20 given by way of example and does not limit the invention. The reference numerals relate to the annexed figures.

Figure 1 is a longitudinal sectional view through the device according to the invention.

Figure 2 is, on a larger scale, a side elevation view of a heating resistance according to a first possible embodiment.
25

Figure 3 is a longitudinal sectional view through a variant of the invention with disassembled components.

Figure 4 is a front elevation view of a
30 cross-section according to line IV-IV in Figure 3 of a resistance according to a variant.

Figures 5, 6 and 7 show schematically three possible arrangements of a pump and a container with water in a device according to the invention.

35

- 3 -

The device according to figure 1 consists of a chamber 1 with two mouthpieces 2 and 3 which are connected to a not represented duct to a machine (a ventilator is usually meant here).

5 The function of an artificial nose (in the technical jargon usually called HME) has been described in broad outline in the introductory portion.

The device by which the heat and moisture losses from an artificial nose can be compensated for, consists therefore of a
10 chambre 1 which can be realized for example by coupling two halves 4 and 5 to which the already mentioned mouthpieces 2 and 3 are connected. Since in normal conditions, i.e. when the air circulates from the left to the right (according to Figures 1 and 3) or vice-versa, the mouthpieces 2 and 3 can be considered alternatively as an inlet and
15 outlet for the air circulating through said chamber. Referring to Figures 3 and 5-7, the patient is located in the direction indicated by a small arrow.

In the supposition that the artificial nose is located in the device at the side of mouthpiece 2, the following succession of components can be seen successively in chamber 1 :

20 a) a bacterial filter 6

b) a hygroscopic material 7 causing a buffer effect. The shape of the hygroscopic material 7 is adapted to the cross-section of chamber 1. In this case the shape of a disk. Each material with important hygroscopic properties can be used herefor.
25 Use can be made of a spongy material or of corrugated paper to which a hygroscopic substance has been added ;

c) a resistance 8, which projects into a metal sleeve 9, is provided at a clear distance from the disk of hygroscopic material 7. Such a sleeve can best be made of aluminium. Although
30 this is not essentially required, it is advisable that a water-absorbent material 10 is applied substantially over the whole length of sleeve 9. A textile can be used hereto but the metal sleeve 9 may be covered with a water-absorbent material. Water is then supplied to the water-absorbent material 10 either directly by gravitation or by means
35 of a pump and this through a duct 11.

- 4 -

The hereabove under c) mentioned resistance 8 is a self-regulating resistance with a 12V source.

In a variant, the self-regulating resistance may be present in the shape of a disk 12 (Figures 3 and 4). Such a disk is cut out of a textile, some of the warp and/or weft threads of which are electrically conductive. The current can be supplied in the way shown in Figure 4, where two conductors 13 and 14 are provided in an arc-shape over a part of the disk. In the supposition that the resistance threads are arranged vertically (according to Figure 4), there will be tension mainly on a vertical middle-strip. If necessary, water can be supplied through a duct 11 to this disk 12 or to the middle-strip of the latter.

The structure of the electrically conductive threads as well as of the other threads allows a regular distribution and therefore also a regular evaporation of the water.

The disk 12 can be clamped between the two halves 4 and 5 composing the chamber 1 or can be fixed to the wall of halve 5 by any appropriate technique known per se.

By a standard choice of the resistances, as well of these which have the shape as shown by figures 1 and 2, as of those which have the shape of disk 12, and by dosing the amount of water reaching these resistance through duct 11 according to the needs, the temperature as well as the humidity of the air inhaled by the patient through the artificial nose can be maintained at the desired level by evaporation.

Supplying water is not essentially required. The hygroscopic material provides for a buffer effect which optimizes the humidity of the circulating air. By heating the air, a larger amount of moisture will condense and will be absorbed by the hygroscopic material so that the moisture loss will be reduced to an acceptable minimum.

Therefore, heat and moisture losses in the artificial nose can be compensated for by technically reliable means which are easy to control.

- 5 -

The buffer effect caused by the hygroscopic material 7, is considerably increased by the presence of a self-regulating resistance according to one of the two hereabove described embodiments at a distance from this material. These resistances are either PTC-or NTC-resistances.

Still according to the spirit of the invention, the here described resistances of the type according to Figure 2 or according to Figure 4, can be mounted completely outside chamber 1. In this case, chamber 1 with the hygroscopic material 7 and the bacterial filter 6 is reduced to the actual artificial nose. The resistance covered by the textile which is in contact with this resistance through the aluminium sleeve 9, or the resistance from the textile which forms the disk 12 and to which water is supplied, is then incorporated in the duct, which has already been put forward hereinabove, between the artificial nose and the patient. When the buffer effect of the hygroscopic material 7 fails or falls out, the effects of the resistance of the type according to Figures 1 and 2 or of the type according to Figure 4 will compensate for the moisture and heat losses in a satisfactory way.

In the device according to the invention, the moisture supply through duct 13 can be dosed by means of a pump 14 which receives the moisture from a container 15. A transformer 16 supplies a low-voltage current to resistance 8, 12, to pump 14 as well as to a programmable unit 17. The programmable unit 7 receives signals from a quick reacting temperature sensor 22 (Fig. 5-7) which detects the flow and the flow times of the air supplied to a patient. The pump 14 may run also continuously at an adjustable flow rate which is situated in practice between 2 and 10 ml/hour. Pump 14 may be omitted if the moisture supply is realized by gravitation as shown by figure 6. In such a variant embodiment, a squeeze-valve 18 is mounted in the water supply duct 13'. The water is delivered from a receiver 19. In this case, programmable unit 17 responds to the squeeze-valve 18.

- 6 -

Finally, moisture (usually water is meant hereby) can be supplied by capillarity to a resistance (for example 8). A possible embodiment based on this principle is shown in Figure 7, wherein a wick 20 supplies the moisture from a container 21 to the
5 resistance 8.

From the hereabove description of the device according to the invention, it is therefore apparent that an excellent solution is provided, by technically simple but reliable means, for the problem consisting in assuring the heat and moisture level in or in
10 combination with an artificial nose.

- 7 -

CLAIMS

1. A device for compensating for the moisture and heat losses from an artificial nose used with a patient, characterized in that it is provided to be incorporated in the duct for supplying air and/or gasses to a patient and that it is composed of a chamber (1) used as actual artificial nose wherein a hygroscopic material (7) serving as a buffer is provided, with means being provided to maintain the air in- and exhaled by the patient, at the required heat level, between the artificial nose and the patient.
2. A device according to claim 1, characterized in that said means is a heating resistance which is located at a distance from said hygroscopic material.
3. A device according to claim 1, characterized in that said means is a heating resistance which is in contact with said hygroscopic material.
4. A device according to anyone of the claims 1 to 3, characterized in that said heating resistance (8, 12) is mounted in said chamber.
5. A device according to anyone of the claims 1 to 3, characterized in that said heating resistance (8, 12) is mounted outside said chamber (1), between this chamber (1) and the patient.
6. A device according to anyone of the claims 1 to 5, characterized in that said heating resistance (8, 12) is a self-regulating heating resistance.
7. A device according to anyone of the claims 1 to 6, characterized in that said heating resistance (8) is externally water-absorbent and in that means are provided for supplying water to this resistance.
8. A device according to anyone of the claims 1 to 7, characterized in that said heating resistance (8) is enclosed by a metal sleeve (9) which is water-absorbent at its outer surface.

9. A device according to claim 8, characterized in that a water-absorbent textile is applied around the metal sleeve (9).

10. A device according to claim 8, characterized in that a water-absorbent material is applied to said metal sleeve (9).

5 11. A device according to anyone of the claims 1 to 10, characterized in that said resistance is a PTC-resistance.

12. A device according to anyone of the claims 1 to 10, characterized in that said resistance is a NTC-resistance.

10 13. A device according to anyone of the claims 1 to 6 and 11 or 12, characterized in that said resistance comprises a disk (12) of textile, at least a portion of the warp and/or weft threads of which are electrically conductive.

15 14. A device according to anyone of the claims 1 to 5 and 7 to 13, characterized in that said heating resistance is provided with a thermostat.

20 15. A device according to anyone of the claims 7 to 14, characterized in that the means for supplying water to said heating resistance are controlled by a pump (14) which receives signals from a quick reacting temperature sensor (22) which detects the flow and the flow time of the air supplied to a patient by means of a ventilator.

16. A device according to claim 15, characterized in that said flow time is detected by means of a temperature sensor (22) and means are provided for sending this information to a programmable unit (17) in order to control said pump (14).

25 17. A device according to either one of claims 15 and 16, characterized in that means are provided for stopping said pump (14) when no air flow is detected by said temperature sensor during a predetermined time unit.

30 18. A device according to anyone of the claims 6 to 17, characterized in that said water supply is realized from a water reservoir.

35 19. A device according to anyone of the claims 6 to 18, characterized in that a squeeze-valve (18) is provided when the water supply is realized by gravitation, which valve is controlled by means dependent on the air flow created in the artificial nose.

- 9 -

20. A device according to claim 19, characterized in that said means comprise a temperature sensor (22) which detects the flow and the flow time of the air supplied to a patient by means of a ventilator.




Fig. 1




Fig. 2




Fig. 4








Fig. 3



INTERNATIONAL SEARCH REPORT

PCT/BE 91/00038

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 A61M16/10 ; A61M16/00		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	A61M	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
Y	FR,A,2 304 359 (TERUMO) October 15, 1976 see page 3, line 9 - line 20 see page 4, line 34 - page 5, line 13; figures 1,2,3 ---	1-8, 10-12,18
Y	EP,A,201 985 (B.O.C.) November 20, 1986 see abstract; figure 2 ---	1-8, 10-12,18
Y	AT,B,320 839 (HIRTZ) February 25, 1975 see page 2, line 38 - line 47; figure 1 ---	3,4
Y	EP,A,258 928 (PONNET ET AL) March 9, 1988 see the whole document in partic. Col 1, line 45- col.2, line 4, fig. 1 ---	6,18
-/-		
¹⁰ Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
12 SEPTEMBER 1991	07. 10. 91	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	PAPONE F. 	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category °	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
Y A	GB,A,1 424 623 (VEB) February 11, 1976 see the whole document ---	7,8,10 15
Y	DE,A,3 311 811 (HIRTZ) October 4, 1984 see page 7, line 5 - line 9; figure 1 ---	11
Y	DE,A,3 818 070 (BOGDANSKI) December 7, 1989 see page 5, line 5 - line 9; figures 1,3 ---	12
A	GB,A,2 176 405 (FISHER & PAYKEL) December 31, 1986 see abstract; figure 1 ---	15
A	US,A,4 363 238 (WILLAM) December 14, 1982 see abstract; figure 1 ---	15,16,20

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

BE 9100038
SA 47837

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12/09/91

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2304359	15-10-76	AU-A- 1217676 BE-A- 839840 CA-A- 1076918 DE-A- 2611898 GB-A- 1539217 SE-B- 419165 SE-A- 7603396 SE-B- 436682 SE-A- 7908070 US-A- 4090513	10-11-77 16-07-76 06-05-80 23-09-76 31-01-79 20-07-81 21-09-76 21-01-85 28-09-79 23-05-78
EP-A-201985	20-11-86	GB-A- 2173274 DE-U- 8606060 FR-A,B 2579896 JP-A- 61232864 US-A- 4686354	08-10-86 17-04-86 10-10-86 17-10-86 11-08-87
AT-B-320839		None	
EP-A-258928	09-03-88	BE-A- 905330	16-12-86
GB-A-1424623	11-02-76	None	
DE-A-3311811	04-10-84	None	
DE-A-3818070	07-12-89	None	
GB-A-2176405	31-12-86	AU-B- 581986 AU-A- 5751386 DE-A- 3617031 FR-A- 2582219 JP-A- 62026076 SE-A- 8602277 US-A- 4708831	09-03-89 27-11-86 18-12-86 28-11-86 04-02-87 23-11-86 24-11-87
US-A-4363238	14-12-82	DE-A- 2933116 AT-T- 2187 EP-A,B 0024327 JP-C- 1585890 JP-B- 2007656	26-02-81 15-01-83 04-03-81 31-10-90 20-02-90